
Section 1 - Product and Company Information

Product Name	Thermablock CR 2000 Part A		
Company	MicroPhase Coatings, Inc	HMIS Code	
Street Address	170 Donmoor Court	Health	2
City, State, Zip	Garner, NC 27529	Flammability	3
Emergency phone:	(800) 424-9300	Reactivity	1
International	001-703-527-3887		

Section 2 - Composition Information/Hazardous Ingredients

<u>Substance Name</u>	<u>CAS #</u>		<u>OSHA Pel</u>	<u>ACGIH TLV</u>
Polydiethoxysiloxane	68412-37-3	<5%	10 ppm	10ppm
Isopropanol	67-63-0	30-50%	400 ppm	400 ppm
Crystalline Sillica	14808-60-7	10-40%	10mg/m ³	0.05
	Respirable crystalline silica can cause silicosis. It is also classified as a carcinogen.			

Section 3 - Physical and Chemical Properties

Boiling Point	82.0 C
Vapor Pressure	NA
Vapor Density (air=1)	> 1
Solubility in Water	reacts
Specific Gravity	<1.00g/cc
Melting Point	NA
Evaporation Rate (Butyl Acetate=1)	NA
Appearance and Odor	white liquid

Section 4 - Fire Fighting Measures

Flash Point	12° C
Autoignition Temperature	399° C
Extinguishing Media	Carbon dioxide, dry chemical powder or appropriate foam. Water spray.
Firefighting	
Protective Equipment	
	Wear self-contained breathing apparatus and protective coating to prevent contact with skin and eyes.
Specific Hazard(s)	
	Liquid material emits irritating fumes under fire conditions.

Section 5 - Reactivity Data

Stability	
	Stable
Materials to Avoid	
	Oxidizing Agents, reacts slowly with moist air.

Hazardous Decomposition or Byproducts

Organic acid vapors, silicon dioxide

Hazardous Polymerization

Will not occur.

Section 6 - Health Hazard Data**Route(s) of Entry**

Inhalation, Ingestion, Dermal

Inhalation

May irritate the respiratory tract, cause headache or nausea.

Health Hazards (Acute and Chronic)

May cause immediate or delayed severe eye irritation. May cause silicosis if inhaled.

Carcinogen

Respirable crystalline silica is classified as a carcinogen. The crystalline silica in this material is blended into a solution. It may become respirable upon spraying.

Signs and Symptoms of Exposure

Irritation of eyes, coughing, skin irritation

Medical Conditions Generally Aggravated by Exposure

Silicosis,

Emergency and First Aid Procedures

Wash skin with large amounts of soap and water. Flush eyes with running water for at least 15 minutes.

If ingested do not induce vomiting, call doctor immediately.

Acute Oral Toxicity ND

Acute Dermal Toxicity ND

Section 7 - Precautions for Safe Handling and Use**Steps to be Taken in Case Material is Released or Spilled**

Use a dry, absorbant material such as sand or vermiculite to absorb material. Transfer to a sealed container for disposal.

Waste Disposal Method

Mix with Part B in the appropriate ratio and allow to cure. Check local ordinances for proper disposal.

Other Precautions

None known.

Section 8 - Control Measures**Respiratory**

NIOSH/MSHA approved respirator.

Hand

Protective rubber gloves.

Eye

Chemical safety goggles or face shield.

General Hygiene Measures

Wash thoroughly after handling.

Section 9 - Transport Information**DOT**

Proper Shipping Name	Flammable Liquid, n.o.s. (Tetraethylsilicate, isopropanol mixture)
	DOT LABEL: FLAMMABLE LIQUID
	DOT ID no.: UN1993
	DOT Hazard Class: 3
	PG: III

Section 10 - Regulatory Information

TSCA All components are included in the EPA Toxic Substances Control Act

ISSUE DATE: 10/11/2005